



## Unix Platforms

### Computer hardware

- CPU: RISC 90 MHz or higher, Intel® 300 MHz or higher
- Memory: 128 MB RAM (256 MB recommended)
- Hard disk space: 100 MB permanent disk space plus 100 MB additional temporary space required during installation
- Network Interface Card: 10baseT or higher, configured with the latest drivers for your platform

### Fax hardware

- Dialogic® Brooktrout® SR140 fax software, TruFax®, TR1034™ digital or analog fax board with Red Hat® Enterprise Linux® 4 and 5 only
- Dialogic® Diva Server™ fax board (Linux only)
- Multitech and Digi fax modem class 2, 2.0, 2.1

### Qualified and recommended platforms

- Sun Solaris SPARC® 9 (32-bit or 64-bit with SPARC v8/32-bit applications support)
- Sun Solaris® Intel 10 (32-bit or 64-bit with x86/32bits applications support)
- IBM® AIX® 5.1 and 6.1
- HP-UX 11i v1 (B.11.11)
- SCO Open Server™ 5.0.7 and 6.0
- SCO UnixWare® 7.1.3
- Red Hat® Enterprise Linux 3, 4 and 5

### Fax Outsourcing

- Fax on Demand Connector to send faxes through the Esker fax service
- Uses HTTPS Internet connection, no proxy server

## Windows Platforms

### Computer hardware

- CPU: Pentium III 450 MHz or Higher
- Memory: 128 MB RAM (256 MB recommended)
- Hard disk space: 120 MB permanent disk space plus 100 MB additional temporary space required during installation
- Network Interface Card: 10baseT or higher, configured with the latest drivers for your platform

### Fax hardware

- Dialogic® Brooktrout® SR140 fax software, TruFax®, TR1034™ digital or analog fax board
- Dialogic® Diva Server™ fax board
- Multitech and Digi fax modem class 2, 2.0, 2.1

### Qualified and recommended platforms

- Microsoft® Windows Server™ 2003 R2 SP2 (32-bit version only) or Microsoft Windows Server™ 2003 SP2 (32-bit Standard Edition, Enterprise Edition, or Datacenter Edition)
- Microsoft Windows Server 2008 SP1 (32-bit and 64-bit Standard Edition, Enterprise Edition, or Datacenter Edition)
- Microsoft Windows XP SP3 (32-bit version only)
- Microsoft Windows Vista SP1 (32-bit and 64-bit versions)

### Fax Outsourcing

- Fax on Demand Connector to send faxes through the Esker fax service
- Uses HTTPS Internet connection, no proxy server

#### For more information:

**Americas** ▪ [www.esker.com](http://www.esker.com)  
**Australia** ▪ [www.esker.com.au](http://www.esker.com.au)  
**France** ▪ [www.esker.fr](http://www.esker.fr)

**Germany** ▪ [www.esker.de](http://www.esker.de)  
**Italy** ▪ [www.esker.it](http://www.esker.it)  
**Singapore** ▪ [www.esker.com.sg](http://www.esker.com.sg)

**Spain** ▪ [www.esker.es](http://www.esker.es)  
**United Kingdom** ▪ [www.esker.co.uk](http://www.esker.co.uk)